

# HQ680

TOUGH CUT



**VENTRAC**

- Connects To Front Of Tractor
- Excellent Visibility
- Cut Material Before Driving Over
- Heavy Duty Deck Construction
- Flip Up Deck

## TOUGH CUT

Model	HQ680
Stock Code	39.55104
Deck Style	Flexible Debris Shield
Width of Cut	68 inches (173 cm)
Number of Blades/Type	3 blades, 5/16 x 2½ x 23 inches (79mm x 6.35cm x 58cm)
Cutting Heights (Standard)	3, 3-5/8, 4¼ inches
Cutting Height Range with Optional Swivel Wheel Kit	3½ - 7 inches (89 to 178 mm) in ½ inch (12.7 mm) increments
Deck Construction	Multi Gauge, 5/16 inch (7.9 mm) at spindle mount
Spindles/Pulleys	Field Serviceable w/ Top Grease Fittings

### Optional Accessory

Swivel Wheel Kit	70.8213
------------------	---------

### Dimensions

Length	45 inches (114 cm)
Width	69 inches (175 cm)
Height	18 inches (46 cm)
Weight	360 lbs (163 kg)
Shipping Weight	449 lbs (204 kg)
Shipping Dimensions (LWH)	73 x 46½ x 19 inches (185 x 118 x 48 cm)

All specifications subject to change without notice or obligation



### STANDARD FEATURES

- Rear Adjustment for Deck Pitch
- Heavy Duty Blades
- Tilt-Up Deck
- Ventrac Mount System

### OPTIONAL ACCESSORIES

- Swivel Wheel Kit

TRACTOR COMPATIBILITY KEY:



The HQ680 Tough Cut is designed for mowing high grass, thick weeds, and heavy brush. A large baffled front opening directs material into the deck and helps hinder debris from escaping.

Three heavy-duty blades counter rotate to cut and deposit waste evenly without windrowing. Capable of tackling saplings up to one inch in diameter, the Tough Cut makes short work out of overgrown thickets.

The Tough Cut can be set to three cutting heights, 3, 3<sup>5</sup>/<sub>8</sub>, and 4<sup>1</sup>/<sub>4</sub> inches. The optional swivel wheel kit provides eight different cutting heights ranging from 3½ to 7 inches.

The HQ680 can be tilted up to access the underside of the mower deck for cleaning, maintenance, or storage. Additionally, easy servicing of belts and pulleys is accessible by the hinged, removable cover.

