

# VENTRAC

presents...

## Snow Blower KX523

**NEW**

For Ventrac 4000 series tractors



### Featuring....

- 2-Stage System
- Double spiral serrated auger
- Double hinged chute deflector with optional electric actuator
- Standard hydraulic controlled
- 220 degree rotation discharge chute
- Extra heavy-duty shaft and bearings
- Chute guard quick release rubber latches
- Chute liners to reduce snow leakage
- Front crossbar protection bumper
- Ventrac Minute Mount System



KX523 with optional Deep Snow Auger Kit



minute  
**MOUNT**  
attachments

**Robust reliability**...efficiency....hydraulic directional chute...**heavy duty** shaft & bearings... front protection bumper...SnoStik tool for dislodging snow....adjustable cast iron skid shoes...quick release rubber latches...ease of use in the most rugged snows....it's about **performance**...it's about **productivity**...the Ventrac KX523 Snow Blower



SnoStik™ for dislodging clogged snow



Double spiral serrated auger



One piece, shaft mounted adjustable cast iron skid shoe discs



3/8" thick abrasive resistant steel adjustable side skid shoes

# VENTRAC DETAILS & SPECS

<b>KX523</b>	
Stock Code	39.55427
Auger	Double spiral serrated
Two Stage	Standard
Paddles	4
Chute	Rotates 220 degrees
Throwing Distance <sup>1</sup>	Approx 35 – 40 feet (10.6-12.2 meters)
<b>Optional Accessories:</b>	
Chute Actuator	70.8025
12 Volt Switch/Plug (required for actuator)	70.4039
Deep Snow Auger Kit	70.8072
<b>Dimensions:</b>	
Length	49 inches (124.5 cm)
Width	52 inches (132 cm)
Height	56.5 inches (144 cm)
Weight	467 pounds (212 kgs)
Shipping Weight	578 pounds (262 kgs)

<sup>1</sup> Dependent on wind and snow conditions

All specifications subject to change without notice or obligation

The 52" wide Ventrac KX523 Snow Blower is built for commercial snow clearing operations of sidewalks, driveways, and other areas. A two stage snow blower, the KX523 features a 16" diameter solid auger for best snow transfer, a large 20" diameter fan, and the ability to move 4500 pounds of snow per minute at distances up to 40 feet. Standard features include adjustable cast iron skid shoe discs at the rear, high carbon hardened steel shoes at the side, and a reversible high carbon hardened steel cutting edge.

The hydraulically activated discharge chute can rotate 220 degrees, all from the convenience of Ventrac's exclusive S.D.L.A. control system. Chute deflection is manually adjustable. An electric chute deflection controller is optional.

