



KD482/602/722 Blades

TRACTOR COMPATIBILITY KEY:

3400

4500



Ventrac KD Power Angle Dozer Blades have working widths of 48, 60, and 72 inches (122, 152, and 183 cm). All control functions are performed with the S.D.L.A. Control for raising and lowering the blade or angling it left or right. Adjustable cast iron skid shoes accommodate dozing at selected heights, such as moving snow on gravel driveways.

Ventrac Power Angle Dozer Blades are versatile, labor saving attachments designed for any number of jobs. From grading, leveling, and backfilling ground to plowing snow, moving material, or cleaning an area, the Ventrac KD series blades are up to the task.

SPECIFICATIONS

	KD482	KD602	KD722
Stock Code	39.55251	39.55252	39.55253
Hydraulic Power Angle	Standard	Standard	Standard
Spring Trip	Mechanical On/Off	Mechanical On/Off	Mechanical On/Off
Hydraulic Cylinder Bore and Stroke	2 x 8 inches (5 x 20 cm)	2 x 8 inches (5 x 20 cm)	2 x 8 inches (5 x 20 cm)
Max Angle (Left/Right)	30 Degrees	30 Degrees	30 Degrees
Ground Clearance	13 inches (33 cm) @ 0 deg.	13 inches (33 cm) @ 0 deg.	13 inches (33 cm) @ 0 deg.
Adjustable Skid Shoes	Standard	Standard	Standard

Optional Accessories

Polyurethane Cutting Edge	44.0207	44.0205	44.0206
Hardened Cutting Edge	78.0057	78.0058	78.0059

Dimensions

Length	27 inches (69 cm)	27 inches (69 cm)	27 inches (69 cm)
Width	48 inches (122 cm)	60 inches (152 cm)	72 inches (183 cm)
Height	22 inches (56 cm)	22 inches (56 cm)	22 inches (56 cm)
Working Width - 0 degrees	48 Inches (122 cm)	60 inches (152 cm)	72 inches (183 cm)
Working Width - 30 degrees	42 inches (107 cm)	52 inches (132 cm)	62 inches (158 cm)
Weight	163 lbs (74 kg)	203 lbs (92 kg)	225 lbs (102 kg)
Shipping Weight	207 lbs (94 kg)	272 lbs (123 kg)	282 lbs (128 kg)
Shipping Dimensions (LWH)	64x24.5x15.6 inches (163x62x40 cm)	76x24.5x15.6 inches (193x62x40 cm)	88x24.5x15.6 inches (224x62x40 cm)

All specifications subject to change without notice or obligation

STANDARD FEATURES

- Hydraulic angle left/right
- Trip Pin locked operation
- Reversible Cutting Edge
- Ventrac Mount System
- Adjustable Cast Iron Skid Shoe Discs
- Greasable center pivot



Adjustable cast iron skid shoe discs

OPTIONAL ACCESSORIES

- Polyurethane Cutting Edge
- Hardened Cutting Edge



500 Venture Drive
Orrville, OH 44667
1.866.836.8722

Fax: 330.683.0000
www.ventrac.com
info@ventrac.com