

KL480

TILLER



- Groundbreaking Power
- Maximum Maneuverability
- Easy To Use
- Heavy Duty Construction
- 48" Working Width

TILLER

Model	KL480
Stock Code	39.55220
Working Width	48 inches (122 cm)
Tines	24
Maximum tilling depth	6 inches (15.24 cm)
Final Drive	#80 Chain, enclosed and lubricated
Ground Clearance	Approx. 10 inches (25.4 cm) raised

Dimensions

Length	41 inches (104 cm)
Width	53 inches (135 cm)
Height	22 inches (56 cm)
Weight	356 lbs (162 kg)
Shipping Weight	425 lbs (193 kg)
Shipping Dimensions (L x W x H)	57x43x25 inches (145x109x64 cm)

All specifications subject to change without notice or obligation



The KL480 Tiller is designed for easy preparation of gardens and yards. This power-driven front-end attachment allows the operator to easily monitor the tiller's performance. Designed with the Ventrac Mount System, the tiller can be attached in a minute or less and comes with a stand for storing when not in use.

A number 80 chain in an enclosed final drive is lubricated for heavy-duty performance. Skid shoe adjustments facilitate cutting depth. Twenty-four high carbon steel tines are sequentially spaced to provide smooth and efficient tillage.

STANDARD FEATURES

- Intermediate Gear Reduction for Quiet Running
- Sealed Lubrication Final Drive
- Leveler Shield
- Adjustable Skid Shoes
- 24 High-Performance Carbon Tines
- Stand for holding attachment when not in use
- Ventrac Mount System

TRACTOR COMPATIBILITY KEY:

3400

4500

