



Power Unit

4200 VXD

4200

The Ventrac **4200VXD** takes compact tractors to an all new level. An articulating and oscillating frame enhances maneuverability and stability over traditional tractors by conforming to the contour of the terrain. The attachment is placed out front in natural view offering greater precision as well as maximum protection for the operator.

Ventrac's patented S.D.L.A. control, located next to the operator, allows for easy control of Speed, Direction, Lift and Auxiliary function all with one hand. Other standard features include Power Steering, Electric PTO with Brake, Easy Shift Operation, Roll Bar with Seat Belt, Comfort Seat and much more...

Over 30 Ventrac attachments let you choose from a variety of tasks. From mowing to blowing, tilling to trenching, digging to drilling, pushing to pulling, Ventrac is designed and built to work when you need it all year round.



Standard Features:

- Liquid Cooled Engines
- All Wheel Drive
- S.D.L.A. controls Speed, Direction, Lift, and Auxiliary hydraulics from a single point
- Heavy Duty Hydrostatic Drive
- Articulation and Oscillating Frame
- Weight Transfer System
- Ventrac Mount System

Optional Accessories:

- Cab
- Foot Control
- Folding Roll Bar - ROPS.
- Strobe/Worklight
- Suspension Seat
- 3 Point Hitch
- AND MORE!



Over 30 Ventrac Mount Attachments



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com

Specifications

Power Unit

4200 VXD

4200

Stock Codes	KT 4200
KT4227 (Kaw. 27hp Gas)	39.51200
KT4226D (B&S Van. 26.5hp Diesel)	39.51204
KT4231TD (B&S Van. 31hp Turbo Diesel)	39.51205

Engines

Kawasaki 27hp gas 2 cyl. (Engine Model FD750D)	Liquid Cooled 746 cc
B&S Vanguard 26.5hp diesel 3 cyl. (Engine Model DM950D)	Liquid Cooled 953 cc
B&S Vanguard 31hp Turbo Diesel (Engine Model DM950DT)	Liquid Cooled 953 cc

Electrical

Battery	450 Cold Cranking amps
Voltage	12 Volts
Alternator	20 amp (Kaw.)/40 amp (Van.)

Powertrain

Hydraulic Pump & Motors	Sauer/Danfoss Series 15
Transaxles	Peerless 2600 Dual Range Transaxles (2)
Hydraulic Oil Cooler	Standard
Hydraulic Oil Filters	2 (10 and 25 micron)

Tires

Standard	Titan HD Fieldtrax (22x12-8 inches) (56x30-20 cm)
Optional Turf Master	Turf Master (22x11-10 inches) (56x28-26 cm)
Optional Bar	Goodyear Rawhide (21x11-8 inches) (53x28-20 cm)

¹Maximum Speeds may vary with tire size, pressure, and engine RPM
All specifications subject to change without notice or obligation

Dimensions	KT 4200
Wheelbase	43 Inches (109 cm)
Length	79 inches (201 cm)
Width w/single Fieldtrax tires	48 inches (122 cm)
Width w/dual Fieldtrax tires	70 inches (178 cm)
Width W/single Turf Master Tires	49 inches (124 cm)
Width W/dual Turf Master Tires	72 inches (183 cm)
Width w/single bar tires	47 inches (119 cm)
Width w/dual bar tire	68 inches (173 cm)
Height (top of Roll Bar)	67 inches (170 cm)
Turning Radius	43 inches (109 cm)
Weight (dependent on engine Type)	1493-1630 lbs (677 -739 kgs)
Fuel Capacity	7.25 Gallons (diesel engines) 6.0 Gallons (gasoline engines)
Travel Speed ¹	
Low Range	5.2 mph (8.4 kph)
High Range	10 mph (16.1 kph)
Shipping Weight w/Crate	
KT4227	1699 lbs (771 Kg)
KT4231	1783 lbs (809 kg)
KT4226D	1817 lbs (824 kg)
KT4231TD	1837 lbs (833 kg)
Shipping Dimensions	79 x 50.5 x 51 inches (201 x 128 x 130 cm)

Instrument Panel

Standard Indicators	Tachometer/Hourmeter, Engine Coolant Temperature, Low Oil Indicator, Voltmeter, Glow Plug Light (diesel), PTO Switch/Indicator Light
---------------------	--

Standard Features

Roll Bar	R.O.P.S. Certified
PTO	Electric Clutch
Steering	Power
Easy Shift	Standard



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com