



Power Unit

3100/3200

3000
series

Good things come in small packages and the same is true for the Ventrac 3100 & 3200.

Now available, these power-packed units feature All-Wheel-Drive, Power Steering, Hydrostatic Drive, and more. The Ventrac Mount System allows you to change attachments quickly and efficiently, moving from job to job with minimal effort.

Equipped with a patented Tandem Drive Train, the 3100 & 3200 efficiently transfers power to where it's needed for unparalleled performance and power.

Also standard on the 3100 & 3200 is Ventrac's patented S.D.L.A. control, which allows for easy control of Speed, Direction, Lift and Auxiliary function all with one hand.

Combine these features with a tight 28 inch (71 cm) turning radius and you will find the 3100 & 3200 can tackle jobs reserved for much larger, less maneuverable machines.



Standard Features:

- All Wheel Drive
- Hydrostatic Drive
- Articulating/Oscillating Frame
- S.D.L.A. Controls
- Foot Pedal

Optional Accessories:

- 12 volt power supply/switch control
- Knobby Tires
- Roll Bar
- Suspension Seat
- Tilt Steering *
- Tractor Cab
- Weight Transfer *

* **RED:** Standard on 3200, optional on 3100



Over 18 Attachments



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC (836.8722)
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com

Specifications

Power Unit 3100/3200

3000 series

	3100	3200
Stock Code	39.31300	39.31405
Engine		
Engine Manufacturer	B&S Vanguard	B&S Vanguard
Horsepower	21 [^]	23.6 ^{^^}
Configuration	2-cylinder	3-cylinder
Cooling	Air Cooled	Liquid Cooled
Operating Engine Speed	1600 - 3200 RPM	
Electrical		
Battery	450 Cold Cranking Amps	
Voltage	12 Volts	
Alternator	50 amp	40 amp
Powertrain		
Type	Hydrostatic (AWD)	
Hydrostatic Transaxles (2)	Hydro-Gear	
Fwd Speed/Rev Speed	7/4 MPH (11.25/6.5kmh), Infinite Variable	
Brakes	Hydro-Dynamic	
Hydraulic Oil Filtration	10 Micron Spin on Filter	
Controls/Instrumentation		
Steering	Power	
Blade Engage/PTO	Electric w/Brake	
Throttle Control/Choke	Cable	
Directional Control	Speed, Directional, Lift, Auxiliary (S.D.L.A.)	
Control Orientation	Hand/Foot	
Gauges	Volt, Hour Meter, Water Temperature**	
Parking Brake/Emergency	Disc	

[^] 20.1 hp gross @ 3200 rpm in the 3121

^{^^} 22.7 hp gross @ 3200 rpm in 3223D

Other Features	3100	3200
Turning Radius	28 inch (71 cm)	
Drive Tires	4 ply Titan Turf 18 x 10.50-10 (46 x 26.67 x 25.4 cm)	
Optional Tire	4 ply Knobby 18 x 11 x 10 inches (46 x 28x 25 cm)	
Fuel Tank Capacity	5.4 gal. (US) (20.4 L)	6 gal. (US) (22.71 L)
Attachment System	Ventrac Mount System	

Dimensions

Wheelbase	38 inches (96.5 cm)	
Length	72 inches (183 cm)	
Width	40.5 inches (103 cm)	
Height	47 inches (119.4 cm)	
Weight (appx)	850 lbs (386 kg)	1050 lbs (476 kg)

Optional Accessories:

12 Volt Switch & Plug.	70.3016
Rear Aux. Hydraulics	70.3018
Rear Weight Bracket	70.3017
Roll Cage	70.3015
Steering Tilt *	70.3019
Suspension Seat	70.3020
Tree Shield kit for use with LQ450	70.3021
Weight Transfer *	70.3014

All specifications subject to change without notice or obligation

* Standard on 3200, Optional on 3100

** On 3200 only, not available on 3100



328 East Water St • PO Box 148 • Orrville, OH 44667
330.683.0075 • 1.866.VENTRAC
Fax: 330.683.0000
www.ventrac.com • info@ventrac.com