

# LM520/600 Side Discharge Finish Mower









## LM520/600 Side Discharge Finish Mower



### **SPECIFICATIONS**

	LM520	LM600
Stock Code	39.35100	39.35101
Deck Type	Front Mount, side discharge	Front Mount, side discharge
Deck Suspension	2 front tires with full width rear roller	
Width of Cut	Approx 52 inches (132 cm)	Approx 60 inches (152 cm)
Number of blades/type	(3) 18 inch (45 cm) Iow lift	(3) 20 ½ inch (52 cm) Iow lift
Cutting Height Range	Approx. 1.5-3.75 inches (3.8-10 cm)	Approx. 1.5-3.75 inches (3.8-10 cm)
Cutting Positions	10	10
Deck Height Adjustment	Single Lever, Quick Select	
Deck Construction	Multi-Gauge, .22 inch (56 mm) at spindle mount	
Spindles/Pulleys	Field Serviceable w/ top grease fittings	
Anti Scalp Roller	Front Center	Front Center
Discharge Deflector	Pivots up with spring tension downward	
<b>Optional Accessory</b>		
Mulch Kit	39.35150	39.35151
Dimensions		
Length	45 inches (114 cm)	45 inches (114 cm)
Width	63 inches (160 cm)	70 inches (177 cm)
Deck Height	13 inches (33 cm)	13 inches (33 cm)
Weight	273 lbs (124 kg)	310 lbs (141 kg)
Shipping Weight	339 lbs (154 kg)	395 lbs (179 lbs)
Shipping Dimensions (LWH)	56x41.5x19 inches (142x105x48 cm)	63.3x47x19 inches (161x119x48 cm)

All specifications subject to change without notice or obligation

#### TRACTOR COMPATIBILITY KEY:



Ventrac LM Side Discharge Finish Mowers have cutting widths of 52 and 60 inches (32, 152 cm) and utilize a rugged all steel frame design, which suspends the Ventrac's discharge deck. This design gives you a high efficiency grass discharge for a better quality of cut by moving more grass efficiently through the deck tunnel. With the removal of two pins beneath the cross frame, the deck can be easily tilted to a near vertical position for maintenance and storage.

These mowers, equipped with a full width rear roller and wide pneumatic front swivel tires float over terrain independent of the tractor. The weight transfer system on the 3400Y (optional on 3400L) reduces mower weight on the ground and increases the traction and stability of the tractor.

LAS, a unique Linear Adjustment System, provides cutting height selections between  $1\frac{1}{2}$  and  $3\frac{3}{4}$  inches (4 and 9.5 cm). A single handle with a slight outward pull allows for a quick and easy change in cutting height selection. A slide release allows the handle to be returned to deck level, preventing it from catching on low branches and shrubs.

All Ventrac LM finish mowers feature a full width rear roller for the ultimate in yard striping. These professional grade mowers are built to give you maximum performance and productivity.

#### **STANDARD FEATURES**

- Flip-Up Deck
- Single-lever Linear
  Adjustment System
- Field-Serviceable Spindles
- Full-Floating Deck
- Ventrac Mount System

#### **OPTIONAL ACCESSORIES**

Mulching Kit







500 Venture Drive Orrville, OH 44667 1.866.836.8722

Fax: 330.683.0000 www.ventrac.com info@ventrac.com