

LQ450 Field Mower









LQ450 Field Mower





SPECIFICATIONS

Stock Code	39.35102
Deck Type	Front Mount, Rear Discharge
Deck Suspensions	Single Center Tire
Width of cut	44.5 inches (approx) (113 cm)
Cutting Heights	2 1/4, 3 1/2, 4 3/4 inches (5.7, 8.9, 12.1 cm)
Deck Height Adjustment	3 snap pins
Deck construction	3/16 inch steel (4.8 mm),
Spindles/Pulleys	Field Serviceable with top grease fittings
Optional Accessories	
Tree Shield Kit for 3100/3200	70.3021
Tree Shield Kit for 3400	70.3047
Rear Weight Bracket	70.3017
Suitcase Weights (Pk 2 Weights)	70.0102
Dimensions	
Length	55 inches (140 cm)
Width	46.5 inches (118 cm)
Height	18 inches (46 cm)
Weight	243 lbs (110 kg)
Shipping Weight	349 lbs (158 kg)
Shipping Dimensions (LWH)	57.5x50x20 inches (146x127x51 cm)

All specifications subject to change without notice or obligation

TRACTOR COMPATIBILITY KEY:



The LQ450 Field Mower is designed to cut heavy grass and small brush growth. Two counter-rotating blades discharge the cut grass to the center rear. Suspended front chains allow tall grass to be cut more effectively and reduce the potential for front discharge. Three pins provide three cutting height options: 2¹/₄, 3¹/₂, and 4³/₄ (5.7, 8.9, and 12.1 cm).

A single swivel tire is located on the front center frame of the field mower. This position greatly reduces tree branch interference. Skid shoes on both sides provide antiscalping and blade protection.

The tree shield kit can be installed for use on tree farms, vineyards, nursery's, etc. This shielding protects both the trees and the operator. Branch lifters and tractor tire covers are standard equipment with the tree shield kit.

Note: The front wheel shields may have to be removed to mount some attachments.

STANDARD FEATURES

- Hydraulic Lift
- 3 Cutting Heights
- Counter Rotating Blades
- Ventrac Mount System

OPTIONAL ACCESSORIES

- Tree Shield Kit
- Rear Weight Bracket
- Rear Suitcase Weights





500 Venture Drive Orrville, OH 44667 1.866.836.8722 Fax: 330.683.0000 www.ventrac.com info@ventrac.com