



# 4200VXD/4100 Features, Accessories, & Attachments

## STANDARD FEATURES (4200VXD/4100)

Full time All Wheel Drive
Front Ventrac Mount System
Articulating and Oscillating frame
<b>Heavy-duty hydrostatic drive system</b>
<ul style="list-style-type: none"> <li>Sauer Danfoss series 15 hydrostatic pump and motors</li> <li>Dual hydraulic oil filtration system               <ul style="list-style-type: none"> <li>25 micron suction filter</li> <li>10 micron pressure filter</li> <li>All oil that may contain contaminants entering the hydraulic system through the auxiliary couplers is filtered before returning to the pump or reservoir (through a 10 micron filter then a 25 micron filter)</li> </ul> </li> <li>EZ oil level check and reservoir fill</li> <li>Hydraulic oil reservoir is mounted above the pump providing a positive flow of oil to the pump during start up and operation</li> <li>Oil Cooler</li> <li>Long life, high performance synthetic oil (HydroTorq)</li> </ul>
<b>Electrical System</b>
<ul style="list-style-type: none"> <li>12 volt, 450 Cold Cranking amps 40 amp alternator on B&amp;S Vanguards, and 20 amp on Kawasaki engines.</li> <li>Halogen Headlights, Tail Lights, Voltmeter, Temperature Gauge (wet engines), Tachometer, and Hour Meter.</li> </ul>
User-friendly S.D.L.A. lever to control Speed, Direction, Lift and Auxiliary hydraulics
HD frame, HD center pivot that is sealed greaseable and replaceable
Comfortable, adjustable, contoured high back operators seat
Certified R.O.P.S. roll bar with seat belt
Storage Compartment
HD electric PTO clutch with brake and operating light
Single lever, high/low shifting from operators seat
Three position control selector for; parking, preference to neutral or "easy shift"
Large 22" X 12" X 8" aggressive flotation turf tires
Parking brake (16 sq in) mounted on front axle
High efficient power steering

## STANDARD FEATURES (4200VXD/4100)

Low front hood line for better visibility
EZ serviceability
Two level foot platform
Front and rear tie downs
O-ring face seals on all high-pressure hoses and fittings to minimize leakage
Front & Rear Skid plates on the transaxles
Powder Coat Paint
2" Receiver-Heavy Duty
43" turning radius
40 mm Heavy Duty Axles

## STANDARD FEATURES ON 4200VXD (but are options on a 4100)

Front Fenders
Weight Transfer System
Four Rear Weights
3 inch Tach/Hour Meter
Front Foot Pegs

## ENGINE OPTIONS FOR 4200VXD (all Liquid Cooled)

<b>4200 LIQUID COOLED</b>	
Kawasaki 27hp Gas 2-cyl	745 cc
B&S Vanguard 26.5hp Dsl 3-cyl	952 cc
B&S Vanguard 31hp Turbo Dsl 3-cyl	952 cc
<b>4100 AIR COOLED</b>	
B&S Vanguard 31hp Gas 2-cyl	895cc



328 East Water St • PO Box 148 • Orrville, OH 44667  
 330.683.0075 • 1.866.VENTRAC (836.8722)  
 Fax: 330.683.0000  
[www.ventrac.com](http://www.ventrac.com) • [info@ventrac.com](mailto:info@ventrac.com)



## 4200VXD/4100 Features, Accessories, & Attachments

### VENTRAC ACCESSORIES for the 4100 & 4200VXD

Arm Rest
Cab
Canopy
Chrome Hub Caps
Dual Wheels; increase width to 70"
Extra auxiliary hydraulics for rear with 3-Point Hitch.
Fold Down Roll Bar - ROPS
Foot Control
Hydraulic Top Link (for 3-Point Hitch)
Racor fuel water separator (standard on diesel)
Rear Bumper
Slope Degree Indicator
Spreader 220 – will spread Seed, Salt, Sand, Fertilizer & Penn Mulch
Strobe & Rear Work Lights
Suspension Seat
<b>Tires</b>
• Bar Tires (21x11-8) Goodyear rawhide
• Turf Tires (22x11-10) Turf Master
Three-N-One Adaptor (Utilize Ventrac NON-PTO powered attachments on the rear 3-Point Hitch)
Three-Point Hitch - Rear category one 3-Point Hitch
Twelve Volt /Twin Plug kit with Cell Phone holder (Installs in Storage Box)
Twelve Volt Switch & Plug Kit, Front
Two-N-One Front Weight Bracket and Tow Hitch
Wheel Extension Kit - to increase tractor width to 54" (Increased Stability)

### VENTRAC ATTACHMENTS for the 4100 & 4200VXD

AERA-vator
Aerator (Core, Fracture, Slicer Tines)
Blades ( 48", 60", 72")
Blower
Broom
Edger
Edger with/ blower
Excavator Bucket ( 30" 48")
Generator 15,000 Watt
Mowers ( 60", 72")
Mower Off Set 72"
Power Rake
Slip Scoops ( 30", 48")
Snow Blower
Stump Grinder
Terra Rake ( 48", 70")
Tiller
Tough Cut Mower (Medium to Heavy Brush)
Trencher
Turbine Blower
V-Blade
Versa-Loader, standard with a 5 cu. ft. bucket
<b>Loader attachments</b>
• Mulch Bucket 9 cu ft
• Tine Forks
• Tree Auger
• Pallet Forks
• Post Hole Digger
• Lift Boom

