



# KV552 V-Blade

TRACTOR COMPATIBILITY KEY:

3400

4500



## HYDRAULICALLY ANGLE EITHER WING



## SPECIFICATIONS

Stock Code	39.55271
Required 12 Volt Switch/Plug Kit for 4500 Tractor	70.4104
Required 12 volt Switch/Plug Kit for 3400 Tractor	70.3036
Hydraulic Power Angle	Independent cylinders
Blade Wing Selection	Electric Solenoid
Spring Trip	Mechanical On/Off
Max Wing Angle (Left/Right)	30 Degrees
Adjustable Skid Shoes	Standard

## Optional Accessories

Top Deflection Flap	70.8044
Flare Kit, 12/6 inch extension (31/15 cm)	70.8046
Straight Extension Kit, 6 inch (15 cm)	70.8047
Polyurethane Cutting Edge	70.8048

## Dimensions

Length, Wings Back	38 inches (96 cm)
Length with 3000 Series Tractor	96.25 inches (244.5 cm)
Length with 4000 Series Tractor	105.75 inches (269 cm)
Width, Wings Back	48 inches (122 cm)
Width, Wings Straight	55 inches (140 cm)
Width, Wings Forward	48.5 inches (123 cm)
Height	24 inches (61 cm)
Weight	240 lbs (109 kg)

All specifications subject to change without notice or obligation

The 55 inch side Ventrac KV552 V-Blade maximizes efficiency with the ability to quickly change from V plow to Scoop to straight blade, all from the convenience of Ventrac's exclusive S.D.L.A. Control System. With a 48" V width, the KV552 is ideal for walks and areas that larger blades are unable to plow.

Standard features include hydraulically activated wing cylinders, mechanical trip, adjustable cast iron skid shoe discs, reversible high carbon hardened steel cutting edges, and a center shoe for gliding over rough terrain. Pivot points are fully greasable to ensure proper operation, even in the worst environments.

The KV552 V-Blade fits Ventrac 3000 and 4000 series tractors, and requires the 12V switch and plug kit.

## STANDARD FEATURES

- Hydraulically angle either wing  
(Requires 12 Volt Switch Plug Kit)
- Adjustable cast iron skid shoe discs
- Adjustable Spring controlled trip mechanism
- Trip Lockout Pin for Digging in material
- Reversible, Changeable Cutting Edge
- Center mounted skid shoe
- Ventrac Mount System

## Optional Accessories

- Top Deflection Flap
- 6 and 12 inch Flare Extension kits
- Polyurethane Cutting Edge



500 Venture Drive  
Orrville, OH 44667  
1.866.836.8722

Fax: 330.683.0000  
www.ventrac.com  
info@ventrac.com